

# PC Fast Ethernet Adapter card Fiber-Link (100Base-FX) 32 Bit

# MICROSENS

## General features

The MICROSENS Fast Ethernet PC adapter card offers the direct connection of end devices to a Fast Ethernet fiber network according to IEEE802.3 standard (Fiber To The Desk).

The connection of the adapter card is done with a duplex fiber with ST or SC connector. Using multimode fiber it is possible to cover distances up to 2 km un full duplex mode. There are extended versions for single mode fibers available. These versions allow transmission distances up to 125 km using full duplex mode.

- 32-bit Bus Master Architecture Support
- PCI bus clock speed range: 16.75 to 40 MHz
- Supports up to 128K bytes Boot ROM
- Wake-On-LAN (WOL) function and remote wake-up (Magic packet, LinkChg and Microsoft wake-up frame)
- Support of half/full-duplex for data rates up to 200Mbit/s
- PCI plug-n-play compatible
- Low CPU utilization
- Provides diagnostic program
- IEEE 802.3u 100BASE-FX compatible
- IEEE 802.3x full-duplex flow control Support
- PCI Specifications Revision 2.2
- Provides status LEDs
- Provides 5 types of fiber connections: multi-mode ST, SC, VF-45, MT-RJ, and single-mode SC

## Driver support

For this card there are several drivers for the different operating systems available. Beside others the following systems are supported:

- NDIS3, NDIS4, NDIS5 for Win95, 98, NT 3.51, 4.0, 5.0, WFW3.11, Windows 2000, Windows XP
- NDIS2 (DOS, OS/2, LANtastic, WFW3.1...)
- NetWare 16-bit ODI driver for DOS, OS/2 and 32-bit ODI driver for NetWare 3.x, 4.x, 5.0 Server
- Packet driver for UNIX Client
- SCO Unix driver
- Linux driver
- DMI support
- Test program for Mass Production
- On-board EEPROM (93C46) Programming Tool  
Setup/Diagnostic Program for DOS/Windows
- RPL Boot ROM for Novell NetWare, Microsoft NT  
PXE Boot ROM

All driver updates can be downloaded from our internet server at:  
**[www.microsens.com](http://www.microsens.com)**

## LED displays




Abb. 1 Status LEDs

## Technical Specifications

<b>Type</b>	Fast Ethernet PC adapter card 100Base-FX (IEEE 802.3u) PCI Bus / Full-Duplex / Plug and Play	
<b>PC Bus</b>	PCI	
<b>Data rate</b>	100 Mbit/s	
<b>Fiber type</b>	Multimode fiber, 62,5/125 µm or 50/125 µm, duplex, with SC connector (ST optional).	
<b>Wavelength</b>	1.300 nm	
<b>Opt. power</b>	-19 dBm (1300 nm multimode min.) -15 dBm (1300 nm single mode min., 15 km version)	
<b>Opt. sensitivity</b>	-30 dBm (1300 nm multimode) -31 dBm (1300 nm single mode, 15 km version)	
<b>Max. distance</b>	Full duplex: 2 km (multimode) 15..125 km (single mode) Half duplex: 412 m	
<b>LED displays</b>	<i>Power</i>	Card ready for operation
	<i>Link</i>	Fiber connection correct
	<i>Activity</i>	Data transmission on fiber port
<b>Operating temp.</b>	0°C to 40°C (32 F- 104 F)	
<b>Storage temp.</b>	-25°C to 70°C (-13 F-158 F)	
<b>Rel. humidity</b>	10% to 90% non condensing	
<b>Dimensions</b>	130 mm x 65 mm (5.12" x 2.56")	

## Order information

Art.-no.	Description	Connectors
MS482641	PC Fast Ethernet adapter card, Boot ROM Option, wake-on-LAN, multimode 1300nm	2xST
MS482642	PC Fast Ethernet adapter card, Boot ROM Option, wake-on-LAN, multimode 1300nm	2xSC
MS482643	PC Fast Ethernet adapter card, Boot ROM Option, wake-on-LAN, multimode 1300nm	1x VF-45
MS482644	PC Fast Ethernet adapter card, Boot ROM Option, wake-on-LAN, multimode 1300nm	1xMT-RJ
MS482647	PC Fast Ethernet adapter card, Boot ROM Option, wake-on-LAN, single mode 1300nm, min. 15 km	2xSC
MS482648	Boot Manage TCP/IP PROM	-
MS482649	Boot Manage PXE PROM	-

Ethernet, Novell, Netware, Microsoft, Windows, Windows for Workgroups, Windows NT , Windows 2000 , Windows XP, SCO, Unix, SUN, Solaris are trademarks of the respective companies. MICROSENS reserves the right to make any changes without further notice to any product to improve reliability, function or design. he/2602